


Model SV is a combination ball valve, wye strainer and union. The 20 mesh stainless steel strainer is removable for cleaning and inspection. The ball valve has a chrome plated ball with Teflon seats, blowout proof stem with double EPDM O-ring seals. The union has an EPDM O-ring seal and tailpiece available in MNPT, FNPT and SWT end connections.

Standard features include Pressure/Temperature Port, Hose End Drain Valve and plugged Bypass Port.



SPECIFICATIONS	
Pressure Ratings:	600 PSI (4140 kPa)
Temperature Ratings:	250°F (121°C)
Body Material:	Forged Brass
End Connections:	Fixed End: DZR Brass - SWT & FNPT Brass - Press End Union End: Brass - SWT, FNPT, MNPT & Press End
Seals:	EPDM
Ball:	Chrome Plated Brass, 100% positive shut off. Optional 316 Stainless Steel.
Stem:	Brass. Optional 316 Stainless Steel.
Handle:	Full size Zinc Plated lever w/Vinyl Grip
Available Options:	"PTV" combination PT & Air Vent, Automatic Air Vent, Handle and Port Extensions



NOMINAL DIMENSIONS & WEIGHTS														
MODEL	SIZE		A		B	C	D	E	**T SWT	Bypass Port-In	Cv*	Flow Range	WEIGHT	
			FNPT	SWT									lbs	kg
SV1e-050	in	0.50"	4.74	4.88	2.99	2.33	1.73	3.53	0.83	.50	5.5	0.35 to 5.0 GPM	1.90	0.86
	mm	15	120.60	124.05	79.95	59.26	43.94	89.87	21.08					
SV1e-075	in	0.75"	4.77	5.22	2.99	2.33	1.73	3.53	0.98				2.67	1.21
	mm	20	121.36	132.66	79.95	59.26	43.94	89.87	24.89					
SV1e-100	in	1.00"	4.91	5.60	2.99	2.33	1.73	3.53	0.98	.50	7.0	0.35 to 13.0 GPM	2.02	0.92
	mm	25	124.79	142.27	79.95	59.26	43.94	89.87	24.89					
SV2e-050	in	0.50"	5.71	5.95	3.86	3.66	2.08	3.72	0.92	.50	7.0	0.35 to 13.0 GPM	2.57	1.17
	mm	15	145.24	151.33	98.04	93.01	52.83	94.64	23.37					
SV2e-075	in	0.75"	5.75	6.20	3.86	3.66	2.08	3.72	1.43				2.61	1.18
	mm	20	146.10	157.56	98.04	93.01	52.83	94.64	36.32					
SV2e-100	in	1.00"	5.96	6.36	3.86	3.66	2.08	3.72	1.17	.50	7.0	0.35 to 13.0 GPM	2.69	1.22
	mm	25	151.59	161.62	98.04	93.01	52.83	94.64	29.72					
SV2e-125	in	1.25"	6.14	6.69	3.86	3.66	2.08	3.72	1.50				2.92	1.32
	mm	32	156.03	170.00	98.04	93.01	52.83	94.64	38.10					
SV3-100	in	1.00"	8.60	9.44	5.62	5.03	2.26	4.78	1.41	.75	25.0	0.35 to 21.0 GPM	4.54	2.06
	mm	25	218.40	239.80	142.90	127.76	57.40	121.40	35.81					
SV3-125	in	1.25"	8.67	9.66	5.62	5.03	2.26	4.78	1.43				4.54	2.06
	mm	32	220.10	245.30	142.90	127.76	57.40	121.40	36.32					
SV3-150	in	1.50"	8.67	9.91	5.62	5.03	2.26	4.78	1.17	.75	25.0	0.35 to 21.0 GPM	4.44	2.01
	mm	40	220.10	251.70	142.90	127.76	57.40	121.40	29.71					

Optional features and accessories available for this Macon product are an extra charge, and not included in the standard model price.

www.maconbalancing.com



Tunstall Corporation
118 Exchange Street · Chicopee, MA 01013
Phone (413) 594-8695 · Fax (413) 598-8109
Section: Components
Bulletin-MB-SV-0915.07

Components - Model SV - 0.50" to 2.00"

NOMINAL DIMENSIONS & WEIGHTS (continued)

MODEL	SIZE		A		B	C	D	E	**T SWT	Bypass Port-In	Cv*	Flow Range	WEIGHT	
			FNPT	SWT									lbs	kg
SV4-150	in	1.50"	9.37	9.91	7.44	5.66	2.83	5.31	1.59	1.25	68.0	22.0 to 70.0 GPM	8.72	3.96
	mm	40	238.00	251.71	188.98	143.76	71.88	134.87	40.38					
SV4-200	in	2.00"	9.56	10.35	7.44	5.66	2.83	5.31	1.50				9.42	4.27
	mm	50	232.16	262.89	188.98	143.76	71.88	134.87	38.10					

* Cv values are for the body only without the screen inside.

** Please reference the tailpiece data sheet #Bulletin-MB-TP for other sizes and connections.

Dimensions not for construction purposes unless certified by factory.

STANDARD COMPONENTS

	PT	Pressure/Temperature test port with brass body, dual durometer EPDM core, threaded brass cap with O-ring seal and neoprene retainer strap. Accepts standard 1/8" (4mm) gauge adapter or thermometer stem. Rated to 500 PSI (3450 kPa) and 275°F (135°C)
	DV	Drain valve with forged brass body, chrome plated ball, Teflon seats, double EPDM O-ring stem seals, aluminum handle, 3/4" hose connection with cap and plastic retainer strap. Rated to 600 PSI (4140 kPa) WOG and 250°F (121°C)

Please reference data sheet #Bulletin-MB-Accessories for optional accessories.

STRAINERS

Optional features and accessories available for this Macon product are an extra charge, and not included in the standard model price.

www.maconbalancing.com



Tunstall Corporation
118 Exchange Street · Chicopee, MA 01013
Phone (413) 594-8695 · Fax (413) 598-8109
Section: *Components* Bulletin-MB-SV-0915.07